

Creating journal (16384 blocks): done

Writing superblocks and filesystem accounting information: done

Different filesystems can also be created using different mkfs command variations.

Mounting and unmounting filesystems

After the filesystem has been created, it can be mounted on the operating system. Follow the underlying steps to mount filesystems-

- Step I: You must know the Universal Unique Identifier (UUID) of your new file system. Use command blkid which will list all the storage devices associated with your system. Search for sda in the output. The process-

```
[root@localhost ~]# blkid
/dev/vda1: UUID="716e713d-4e91-4186-81fd-c6cfa1b0974d"
TYPE="xfs"
/dev/sr1: UUID="2019-03-08-16-17-02-00" LABEL="config-2"
TYPE="iso9660"
/dev/sda: UUID="wow9N8-dX2d-ETN4-zK09-Gr1k-qCVF-eCerbF"
TYPE="LVM2_member"
/dev/mapper/test-test1: PTTYPE="dos"
/dev/sda1: UUID="ac96b366-0cdd-4e4c-9493-bb93531be644"
TYPE="ext4"
```

```
[root@localhost ~]#
```

- Step II: To mount the sda device, run the command line as follows:

```
[root@localhost ~]# mkdir /mnt/mount_point_for_dev_sda
[root@localhost ~]# ls /mnt/
mount_point_for_dev_sda
[root@localhost ~]# mount -t ext4 /dev/sda1 /mnt/mount_point_for_dev_sda/
```

```
[root@localhost ~]# df -h
```

Filesystem	Size	Used	Avail	Use%	Mounted on
/dev/vda1	7.9G	920M	7.0G	12%	/
devtmpfs	443M	0	443M	0%	/dev
tmpfs	463M	0	463M	0%	/dev/shm
tmpfs	463M	30M	434M	7%	/run
tmpfs	463M	0	463M	0%	/sys/fs/cgroup
tmpfs	93M	0	93M	0%	/run/user/0
/dev/sda	2.9G	9.0M	2.7G	1%	/mnt/mount_point_for_dev_sda

```
[root@localhost ~]#
```

The df -h command displays the individual mount points for respective