

filesystems. In the list of the mount points, search /dev/sda. Substitute it with the UUID which we got as output using the blkid command.

- Step III: Using mount command directly on the command line (as in Step II) is having an issue that the mount will not persist across reboots. To mount the filesystem persistently, edit the /etc/fstab file to include your mount information: `UUID=ac96b366-0cdd-4e4c-9493-bb93531be644 /mnt/mount_point_for_dev_sda1 ext4 defaults 0 0`

- Step IV: Unmounting Filesystem

After you edit /etc/fstab, you can umount /mnt/mount_point_for_dev_sda1 and run the command mount -a to mount everything listed in /etc/fstab. If everything went right, you can still list df -h and see your filesystem mounted:

- `[root@localhost ~]# umount /mnt/mount_point_for_dev_sda1/`
- `[root@localhost ~]# mount -a`
- `[root@localhost ~]# df -h`
- | Filesystem | Size | Used | Avail | Use% | Mounted on |
|------------|------|------|-------|------|------------------------------|
| /dev/vda1 | 7.9G | 920M | 7.0G | 12% | / |
| devtmpfs | 443M | 0 | 443M | 0% | /dev |
| tmpfs | 463M | 0 | 463M | 0% | /dev/shm |
| tmpfs | 463M | 30M | 434M | 7% | /run |
| tmpfs | 463M | 0 | 463M | 0% | /sys/fs/cgroup |
| tmpfs | 93M | 0 | 93M | 0% | /run/user/0 |
| /dev/sda | 2.9G | 9.0M | 2.7G | 1% | /mnt/mount_point_for_dev_sda |
- Step V: You can also check whether the filesystem was mounted:
- `[root@localhost ~]# mount | grep ^/dev/sd`
- `/dev/sda on /mnt/mount_point_for_dev_sda type ext4 (rw,relatime,seclabel,stripe=8191,data=ordered)`

Playing with CD-ROM images such as .ISO files

.ISO image is an archive file (disk image) of an optical disc. It generally uses a conventional ISO format. File extension of ISO image files is .ISO. You can mount an ISO file or images via the loop device under Linux. It is possible to specify transfer functions (for encryption/decryption or other purposes) using the loop devices.

Steps to mount .ISO files in Linux:

- This command creates a mount point directory for .ISO files on Linux-
`sudo mkdir /mnt/iso`
- To mount .ISO file on Linux use the following command-