

and the Rigid Body 2D components in the Inspector panel, to the Ship_B_laser GameObject. Make sure that the X and Y dimension values in the Capsule Collider 2D component matches with the X and Y dimension values of the projectile used for Player 1 ship, otherwise one of the two ships will have an advantage in terms of more effective area of projectile interaction, or in simpler terms, larger bullets. Make sure to change the Gravity attribute in the Rigid Body 2D component to 0, like every object in the scene with that component. In the Transform component, which is added by default,



Twice the Pew Pew!

change the dimensions of the X and Y attributes to the dimensions used for the projectile of Player 1. Note that the Rigid Body 2D component attribute dimensions scale relative to the Transform component attribute dimensions are tweaked. Add the Bullet Attribute (Script) component, and your projectile for Player 2 is ready. Drag it from the Hierarchy panel to the Project panel to convert it into a prefab, and then delete the Ship_B_laser GameObject from the Hierarchy panel.

Right click on ShipB, and Create Empty GameObject. Rename this object BlasterB. Click on Add Component, and look for Object Shooter, and add it. Change the Key To Press attribute to Right Shift. If you remember, the Key To Press attribute for ShipA was Left Shift. In the Object Shooter component, change the X value to 0, and leave the Y value at 1. In the Transform component, move the blaster to the nose of ShipB. Note that this value does not, and should not be the same value used in the Transform component of ShipA. It entirely depends on the particular geometry of the spacecraft. The Creation Rate and the Shoot Speed values of the Object Shooter component should match the corresponding values of the Object Shooter component of BlasterA. Drag and drop the Ship_B_laser prefab to the Prefab To Spawn