

- Suppose you are using the Mac device, then you have to go to the system preferences > network. Then you have to click on the advanced option, which is seen on the bottom right corner of the device. Later in the top of your next window, you can check out the TCP/IP option, just make a click on it and then find out the IP address of the router.
- In case you are using an iPhone, then go to the settings option > Wi-Fi and then click the “i” icon which is found next to the network which you have connected to. There your IP address of the router will be listed.

Procedure to secure your Wi-Fi:

You can very quickly secure your Wi-Fi, and it will help you to prevent your files from hackers and then prevent others from accessing your internet. There are certain procedures which you can use to secure your Wi-Fi connection very easily.

- **Procedure 1: Open the router settings page:**

Know the right process to access the settings of your wireless router effectively. You are able to do this correctly by typing “192.168.1.1” into your browser, and after that, you have to enter your username and password for your router. You can check your router’s user manual or the back of your router for the username and password.

- **Procedure 2: Create a strong and unique password:**

The next procedure for securing your wireless network is creating a strong password on your router. The primary thing you have to do after logging into the router is change the default password to your unique password.

- **Procedure 3: Enable network encryption:**

There are an enormous number of encryption techniques available for the wireless settings, which include WPA Personal – WPA, Wi-Fi Protected Access version 2 – WPA2 and WEP. WPA 2 is the most secure one which is compatible with hardware that is manufactured post the year 2006.

Don’t forget to use a combination of numbers, special characters, and letters in your password.

- **Procedure 4: Filter the MAC addresses:**

If you are having a Wi-Fi-enabled cell phone or laptop, then all the wireless devices should have a unique MAC address. You can add the MAC address