

- /usr/bin/which: no cd in (/opt/jre1.6.0_03/bin:/usr/lib/qt3.3/bin:/usr/kerberos/bin:/opt/jre1.6.0_03/bin:/usr/lib/ccache:/usr/l
- ocal/bin:/usr/bin:/bin:/home/me/bin)

The result displays that the cd command was not found in all the listed directories in the bash.

Note: Though if found in the system, the results will give us the location.

- [me@linuxbox ~]\$ which cd
- /usr/bin/cd

Knowing Command documentation

After identification, users need to know the documentation for a specific command. Linux has several commands to inform users about the use of commands.

help command – for shell builtins

Linux bash offers several types of built-in support for each shell builtins. You can use them by typing 'help' and then the command name. Here is a quick demonstration of the help command:

- [me@linuxbox ~]\$ help cd
- cd: cd [-L|[-P [-e]]] [dir]

Change the shell working directory.

Change the current directory to DIR. The default DIR is the value of the HOME shell variable.

The variable CDPATH defines the search path for the directory containing DIR. A colon separates alternative directory names in CDPATH (.). A null directory name is the same as the current directory. If DIR begins with a slash (/), then CDPATH is not used. If the directory is not found, and the shell option `cdable_vars' is set, the word is assumed to be a variable name. If that variable has a value, its value is used for DIR. Options:

- L forces symbolic links to be followed
- P use the physical directory structure without following symbolic links
- e if the -P option is supplied, and the current working directory cannot be determined successfully, exit with a non-zero status.

The default is to follow symbolic links, as if '-L' were specified. Exit Status: Returns 0 if the directory is changed, and if \$PWD is set successfully when -P is used; non-zero otherwise. Here, square notation: cd: cd [-L|[-P [-e]]] [dir] are the optional items you can use with the command while the vertical bar stands for mutually exclusive items. So, this notation for cd command