

You can also check the permissions through `umask` command. For example, when we create a file in the `temp` directory

- `Cd/ temp`
- `Touch newfile`
- `Ls -l newfile`

We get an output like this one:

- `-rw -r---r-`

Here the user who has created the file can read and write, the group to which the user belongs can only read and accordingly, all others can read-only. The octal value for this `umask` is `0022`. To check this value using `umask` command,:

- `Umask`

You will get the output `0022`

Moreover, you may have file processes and daemons, and you may want to manage the permissions on those files. In this case the question is who shares the same Apache group? In general, you should place the `umask` command in the script used to run the daemon or in the first included file. So for Apache this is environment includes `/ etc / apache2 / envvars`. You can now execute the command-

- `Umask 002`

And restart your apache.

The su command in Linux.

In Linux, the command '`su`' is used to switch over from one user account to another. When you enter the `su` command, you will be prompted to enter the password for the user to whose account you want to switch. For instance, you want to switch over to the user account, Mary. Then use this command-

- `Su Mary`

The `su` command can also be used to switch over to the root account. Here, you have to enter the `su` command without any parameters or arguments:

- `Su`

You will be prompted to enter the password for the root user. The arguments, which are commonly used while invoking the `su` command are `-`, `-s`, and `-login`. For instance, if you desire to run a login shell similar to the real login and simultaneously change the current directory, enter this command:

- `Su -`

You can use the `--` argument to separate `su` option from other arguments that are present in the shell. If necessary, the user is asked to enter a password. Invalid password generates an error message. All valid and invalid attempts