

Selenium official website, you can access all the language bindings you are looking for.

2. JSON Wire Protocol

The use of the JSON wire protocol is a significant web driver used as a mode of communication between client libraries and drivers. JSON stands for Javascript Object Notation that also supports varieties of data structure to make the process of reading and writing data from JSON easier.

3. Browser Drivers

Selenium provides drivers with every single application. The application driver communicates with the user by maintaining a safe link without disclosing the inner workings in the browser operations. Such application drivers are also unique to the language that used code test cases, such as C #, Python, Java, etc.

The device driver you pick can be updated according to your language specifications. For instance, on BrowserStack, you can set up Python's selenium web driver.

When using WebDriver, a test script carries out the following tasks in the background, such as:

- i. For each Selenium Command, an HTTP request is generated and then sent to the browser driver.
- ii. The driver receives the HTTP application via the HTTP server.
- iii. An HTTP server decides on all steps/instructions performed in the browser.
- iv. The execution state would then be forwarded to the HTTP server and from there to the automation scripts.

Steps to help you understand the Selenium test process

You can apply the following seven basic elements of a test script for Selenium to every test case and application under test (AUT):

1. Starting with a WebDriver instance.
2. Browsing to a Web page.
3. Locating the web page and its HTML components.
4. Modifying HTML elements
5. Evaluating the Browser response to changes
6. Building a test framework to run specific tests and track results
7. Finishing the test