

1. Starting with a WebDriver Interface

The WebDriver interface provides the basis for all implementations with the Selenium WebDriver API. The first phase of creating the Selenium test is to initialize the WebDriver interface.

By using a constructor for a particular Web browser, you can build an instance of WebDriver interface. The names of such constructors are different over web browsers. Alongside this, the construction invocations vary across programming languages.

Utilize this instance to invoke operations and access the further interfaces used in the elementary steps after you generate the WebDriver interface instance.

Have a look at the example below-

```
• import org.openqa.selenium.WebDriver;
• import org.openqa.selenium.firefox.FirefoxDriver;
• WebDriver driver = new FirefoxDriver();
```

2. Browsing to a web page

The next move is to browse to the website that you need to check after you have instantiated WebDriver. However, you can start this by utilising the get method of the WebDriver interface unique-instance.

However, this method is used explicitly on driver variables. The get method takes the page URL as the statement that you would like to check. It can either be a specific string value or a particular instance of a URL.

Below is an example that uses a path to enter the Web page on www.example.com using the driver variable and passes a string argument attribute with relation to its URL. In the SeleniumHQ documentation, you may find other examples too.

```
• driver.get("http://www.example.com");
```

3. Locating the web page and Its HTML components

Now, you should find HTML objects on the URL. Then, undertake actions on these elements such as the text entry (for text access) or clicking (in case of button elements) that helps users to communicate with a web-page effectively.

The SeleniumHQ documentation provides extensive details regarding the various HTML location methods, which sums up the most standard strategies.