

back to the Spider that has issued the request. Both the classes of request and response have sub-classes that add features that are not required in the final base class or classes.

To deliver a user response to any specific system and send the response back to a user, Application Programming Interfaces or APIs are used. It helps users to manage a website or its components and align microservices in relation to the same. They offer a wide range of advantages for e-commerce platforms and help users navigate services and available solutions easily. The requests of classes and response subclasses are mentioned below:

What is Response Time Testing?

Response time testing is a measure that can be used to calculate the time required by one system to respond to the requests of another system. In other words, it refers to a time measure that is not required to reach out to a specific input or action until the action is completed, for example, for an application API, if you want to know how much time it requires to execute and return the data in JSON. Response time testing measures the server response of every single query or transaction. Usually, it starts when a user transmits a request and finishes it at the time. Various test tools can be used to measure the response time by surrounding the crucial business process from its start and end. Any application process might just be an action or a collective set of actions that users perform to finish developing their apps.

Request Objects

A “Request” object alludes to an HTTP request that is basically created in the Spider and executed by a user. Thus it generates a “Response”. The REST framework offers request objects that seamlessly extend regular HTTP requests and offer comparatively more flexible request parsing. The core function of this request object is the attribute known as the request.data, which is quite similar to the method of request.POST. This method is more useful than working with web applications or APIs. The parameters of the request objects are inclusive of the following:

- **URL (String)**- If the URL of the request objects is invalid, then a “ValueError” exception is generated.
- **Call Back**- It is a function that is called along with the response of the object request as the first parameter once it is downloaded. If the