

- **Web Servers-** The web server affects HTTP object response construction.

Response Object

A “Response” Object represents the HTTP response, which is basically downloaded by a user and sent to the Spider for further processing. The REST framework also offers a response object, which is just a type of template response that aligns with the branded content or content negotiation to determine the type of content and return it to the client. Some of its parameters are:

- **URL (String)-** It is the URL of the response object.
- **Status (Integer)-** It is the HTTP status of the response object that defaults to 200.
- **Headers (Dict)-** It is the header of the response and its values can be string or list that is for single or multi-value headers.
- **Body (Bytes)-** It is the response body that accesses the decoded text message that users can use from any encoding-aware Response subclass.
- **Flags (List)-** It is a list of initial values for the response flag attribute. If given this list, it can be shallow copied.
- **Request (scrappy.http .Request)-** It is the initial value of the response request attribute representing the request to be generated.
- **Certificate (twisted.internet.ssl.certificate)-** An object certificate represents the SSL certificate of the server.
- **IP Address-** It is the IP address of the server from which the response has originated.

Usually, users do not return the HTTP object response directly from the view. Rather, they prefer modifying the existing response object that is associated with the request and return the object response which will be the HTTP response payload. The HTTP response payload object can be either of

- A string.
- An iterable where the response gets a string instead of getting memory buffered.

Response Body

A user might want to manipulate or read the response object body in the post-construction. The response body cannot always be a string;