

rather, it can be iterable or a generator for the data. Users can change the response body with the help of the `setBody` command and lock it further.

If `lock=true`, then no further modification in the HTTP response body is allowed, and it will instantly fail.

Status Line

The start line of any HTTP response is known as the 'Status Line' which is inclusive of information such as the following:

- The protocol version.
 - A status code which indicates the success or failure of the corresponding request. Common status codes for the responses are 200, 404, 302.
 - Or status text, which in short is your information or textual description of the status line that helps users to understand the HTTP message.
- Any typical status line may look like- [http/1.1](http://1.1) 404 Not Found.

Response Subclasses

Given below is the list of built-in available response subclasses. These subclasses can be organised by users to implement their own functions.

TextResponse Objects

`TextResponse` object and encoding functions to the base response class which is ultimately meant to be utilised for binary data like images and sound or media files. This object also supports new method arguments along with the base response objects. Its remaining function is similar to that of the response class, and it doesn't get documented here.

Parameters

Encoding is a string containing various parameters to be used for the response object. If one creates a text response object with a Unicode body, then it gets encoded using the same encoding where the body attribute is always categorised as a string. If encoding is the default value (i.e. none), then the response object headers and body are considered instead. The text to response objects also support the following attributes along with the standard response objects:

- **Text-** The response body here is a unique code which is the same as the `response.body.decode(response.encoding)`. But its results are cached after the initial call so users can easily access the response.