

text multiple times without any overheads. The Unicode (response body) is not a suitable measure to convert the response body object to Unicode.

- **Encoding-** A string with the essential encoding is resolved by trying several mechanisms, such as
 - Encoding gets passed in `_init_` method encoding augment.
 - The encoding gets declared in the Content-Type HTTP header and if the encoding becomes invalid then it is ignored.
 - The encoding gets declared in the response body where the `TextResponse` doesn't offer any special features for the same.
 - The encoding is infected by considering the response body which is a more fragile methodology.
- **Selector-** A selector instance is used as a target by the response object and it is lazily instantiated in the first access. The `TextResponse` object also supports various methods to the standard response. These are
 - XPath
 - CSS
 - follow
 - follow_all
 - JSON

A generator that creates request instances to follow through the links in the URL accepts the same arguments from the request's methods, except for the URL that doesn't require an absolute URL. It can be any of the following components:

- A relative URL
- A link object the link extractors
- A selected object for the link element
- An attribute selector

In addition, the XPath and CSS arguments get accepted to execute the link extraction within the method where the commands are accepted.

HTML Response Objects

The HTML Response Objects is the subclass of Text Response, which adds encoding auto-discovering system support by considering HTML HTTP attributes.

XML Response Objects

The XML Response class is the subclass of text response that adds