

polls/models.py

```

from django.db import models

class Question(models.Model):
    question_text = models.CharField(max_length=200)
    pub_date = models.DateTimeField('date published')

class Choice(models.Model):
    question = models.ForeignKey(Question,
    on_delete=models.CASCADE)
    choice_text = models.CharField(max_length=200)
    votes = models.IntegerField(default=0)

```

these values are used in Python coding. The databases will use these names as their column names.

If you want to designate any field as a human-readable name, then there is an option of first position argument. This is used in Django's introspective parts. It also doubles as documentation. In case this field is not provided, Django will automatically use the machine-readable names.

In our example, `Question.pub_date` is defined by us, and that is a human-readable naming. Also, for other fields that are used in our model, we have the machine-readable names as a sufficient naming option because they are also human-readable names. Also, Field classes are there, and they require arguments. For example, the field `CharField` needs you to provide a `max_length`. These are used in Database Schema and into validations. Here, Fields may have several optional arguments too. In our case, what we've is the set of the default values for field votes to be Zero.

Finally, 'ForeignKey' is used to define relationships. These relationships tell the Django framework that each Choice (field) is systematically related to one single Question. Also, Django largely supports all common database relationships such as many-to-many, many-to-one and one-to-one.

Model Activation

These small chunks of the model code tell Django a lot of details. With that short model code, Django can perform the following operations: