

file. You can replace the installed boot1 and boot2 by interrupting the boot process and using necessary commands.

Stage 3: The Stage 3 or the loader is in the file system of the disc. The loader serves as an interactive method for configuration. The FreeBSD system usually uses a built-in command set. You can also use an interrupter that has a more complex command set. Initially, the loader probes for the console and disc determine from which disc it is booting. As the loader sets variables, you get an interrupter to use commands. You can choose commands from a script or make it interactively. By the end of this stage, the loader waits for 10 seconds to check with the interruption. If you don't enter any command, it boots the kernel. If you interrupt, you get a prompt wherein you can enter the commands. You can use commands to load a module, unload all modules, and to adjust variables. Finally, reboot to get the desired mode.

Stage 4: As the loader or boot2 load kernel, it checks for boot flags, and adjusts the behaviour accordingly. Upon booting, kernel passes the control to the user process.

Single-user and multi-user mode

Usually, professionals use single-user mode in case of repairs due to an error. If your system doesn't boot due to irregularities in a boot configuration file, using single-user mode is preferable.

To avoid a security breach, the system asks for a root password before initialising the single-user mode. You can specify the single-user mode by booting with `-s`. Another option is setting the `boot_single` variable in the loader. Again, if you are in multi-user mode, you can run shutdown now from there to reach the single-user mode.



Configuration during booting FreeBSD

Copyright attribution: Image From
Pixels By Negative Space

If the user inputs `exit` from the single-user mode after completing the commands or if `init` finds the file systems in order, the system goes into multi-user mode. The resource configuration system reads the configuration defaults, system-specific details and mounts system files. The networking services, miscellaneous daemons and startup of