

Basically, a combination of various data backup techniques is used. For instance, one can develop a schedule to automate the periodic reporting system backup that is stored off-site.

File system backup

The conventional UNIX program for file system backup is `dump`, which creates the backup, while you can use `restore` to restore a backup created with `dump`. These programs work at the disc block level, below the

file, directory, or link abstractions. Unlike other backup solutions, `dump` can backup the entire file system, and it is incapable of restoring the part of the system or a directory tree. Instead of trying to copy files and directories, `dump` creates a copy of the raw data on a drive.

Note: If `dump` is used in the root directory, it will not back up `/home/` `usr` or other directories as they are typically mounted points for various other file systems.

When the `restore` program is used to restore the data, then it stores temporary files by default. In fact, during recovery, this program is used with a small `/tmp` set. You should set `TMPDR` to a directory with extra free space to restore the data successfully. While using the `dump` program, it is important to consider a few quirks from its initial days in version 6. The default parameters perceive backup to a 9-track tape instead of any other media type or high-density tapes. These default devices can be overridden on the command line.

It is possible to back up the filesystem across various networks in another system or to tape the drives attached with other systems. The `dump` and `restore` programs can be used to fulfil this purpose that is not considered to be protected.

Rather, one can use `dump` and `restore` utilities in a secure fashion over the SSH secure connection. This example develops a compressed and full backup of `/usr` and sends the backup file to a specific host over the SSH connection:



Backup basics

Copyright: ctrl.blog/