
```
# The Directory to store downloaded updates
# files used to update FreeBSD
# WorkDir /var/db/freebsd-update
```

It is this directory which houses all the temporary files along with patches. In case you want to upgrade, you require at least a gigabyte of free space.

```
# While upgrading in-between releases, the components list can include
# read as StrictComponents yes or only as a list of components
# which *might* be installed of which FreeBSD Update should figure out
# which are installed and upgrade those (StrictComponents no)?
# StrictComponents no
```

If this option is marked as yes, the FreeBSD-update will consider the list of complete components and wouldn't make any change from items outside the list.

The `FreeBSD-update` command will try and update every file which is present in the components list.

Note: Before using a FreeBSD-update, you can ensure that a copy of the Generic kernel is present in `/boot/GENERIC`. In the case of a custom kernel, if it has been built only once, the kernel in `/boot/kernel.old` is the GENERIC kernel. You can rename this directory to `/boot/kernel`.

Working with security patches

Using FreeBSD security patches is made simple by allowing the administrator to keep the system updated with a `FreeBSD-update`.

You can use the following commands to download and install security patches. The mentioned command will allow you to determine any existing patches, and in case, it will provide a list of files to be modified after applying the patch. The mentioned second command will move ahead and use the patches.

```
# freebsd-update fetch
# freebsd-update install
```
