

- It can restore a previously made package database backup through the command `# pkg backup -r location` (where `location` is the location of the backup).
- It can remove packages that are outdated through `# pkg clean`.
- It can modify the package's metadata through `# pkg set -o data` (where `data` is the information to be modified).

Ports collection

The Ports Collection is among the most important entities in FreeBSD if you are working with third-party software. It contains a list of ports that can be used to install third-party programs to your system to work with Ports Collection, and you first need to install it. For this, there are two methods in FreeBSD – the Portsnap method and the Subversion method.

Once the Ports Collection has been loaded, you need to know how to use it. The Ports Collection contains software categories in the form of directories. Each of these categories contains associated software that can be installed with the help of a command.

To install a particular port, you first need to change the directory to where that port is located. Now, give the `make install` command, and your port will be installed automatically.

You can also remove ports with the help of the Ports Collection. The process is similar to that of installation. Go to the directory in the Ports Collection where the port is located, and give the `make deinstall` command.

You can also upgrade ports using the ports collection. For this, the two methods involve applications called Portmaster and Portupgrade. These can be installed through the Ports Collection itself.



Ports Collection in FreeBSD

Copyright Attribution: hostleadadmin

Building packages

If you are an advanced user of FreeBSD, you can also choose to build and install your self-created FreeBSD compatible packages. The licensed utility