

LCD works with three colour lights – red, green-blue. They are small in size, affordable, use less energy, and produce a wide range of colours with greater accuracy than CRT.

One can use the following configuration to set up the resolution of monitors:

run `xrandr` without any parameters to see a list of video outputs and detected monitor modes:

```
% xrandr
```

Our configuration shows that the system utilises DVI-O output to display screen resolution of 1920x1200 and the refresh rate is 60Hz. Yours will be unique to your system.



Monitors

Copyright Attribution: Photo by Computer Hope is licensed under CC BY-NC-SA

How to setup fonts in Xorg

XOrg renders TrueType fonts efficiently as it is inbuilt. Two different models can enable this function. You can use the following FreeType model by adding this line to the `Module` section of `/etc/X11/Xorg.conf`.

Load “FreeType”

Next, make a directory for TrueType fonts (for e.g., `/USB/local/fonts/TrueType`) and copy all the fonts to this location. TrueType fonts can't be taken directly from Apple operating systems; it has to be MSDOS/UNIX/LINUX or Windows. After the fonts are copied into the directory, use `mkfontscale` to develop `fonts.dir`, so that the X window system knows the new files are installed.

`mkfontscale` can be installed online in form of a package:

```
# pkg install mkfontscale
```

Then create an index of X font files in a file location or directory:

```
# cd /usr/local/share/  
fonts/TrueType
```

```
# mkfontscale
```

Now add the TrueType® directory to the font path:

```
% xset fp+ /usr/local/  
share/fonts/TrueType
```

```
% xset fp rehash
```



TrueType

Bitmap

True Type

Copyright Attribution: Photo by CS Exhibitions is licensed under CC BY-NC-SA