

If you don't remember whether you have turned on the default compatibility or want to check if the module is loaded appropriately, verify by typing the following line:

```
% kldstat
```

If the module is loaded, it will show the following output:

Id	Refs	Address	Size	Name
1	2	0xc0100000	16bdb8	kernel
7	1	0xc24db000	d000	linux.ko

Once you know that the module is loaded successfully, you can start by installing Linux Libraries.

● Installing Linux Libraries

You can install Linux libraries in two different ways: by using `linux_base` port or manually. There is a possibility that even after installing libraries from the `linux_base` port, the system may ask you for additional shared libraries. Installing other shared libraries is similar to manual installation. We will be individually going through both the possibilities.

1. Installing Linux Libraries by Using Linux_Base Port

Linux has a default port collection for installing libraries. It is one of the easiest ways to install libraries and make Linux binary compatible as it only requires you to run two lines of code. Here's how you can install libraries from the `linux_base` port.

- `# cd /usr/ports/emulators/linux_base`
- `# make install distclean`

In the first line in the above code, you will find "linux_base." There can be multiple versions of this port available, such as `linux_base-c7`, each for different Linux distributions. It will help if you select and install the port version that meets your application program's requirements.

2. Installing Linux Libraries Manually

To install Linux libraries manually, you will have to check the list of shared libraries needed by your program to run. You can find the required shared libraries with the `ldd` command if you have root access to the Linux system. For instance, to check `linuxdoom` required shared libraries, you can run the following command where the `Doom` is installed:

- `% ldd linuxdoom`

This command will give you the following outputs: