

- `libXt.so.3` (DLL Jump 3.1) => `/usr/X11/lib/libXt.so.3.1.0`
- `libX11.so.3` (DLL Jump 3.1) => `/usr/X11/lib/libX11.so.3.1.0`
- `libc.so.4` (DLL Jump 4.5pl26) => `/lib/libc.so.4.6.29`

```

== 00000 root [swapper]
|-- 00001 root /sbin/init --
| |-- 00196 root /sbin/devd
| |-- 00230 root /usr/sbin/syslogd -s
| |-- 00344 root sendmail: accepting connections (sendmail)
| |-- 00348 smmnp sendmail: Queue runner#00:38:00 for /var/spool/clientmqueue
| |-- 00354 root /usr/sbin/cron -s
| |-- 00439 _dhcp dhclient: ed0 (dhclient)
| |-- 00391 root login ipam! (login)
| |-- 00400 root -csh (csh)
| |-- 00701 root /usr/local/bin/pstree
| |-- 00703 root sh -c ps -axsso user,pid,ppid,pgid,command
| |-- 00704 root ps -axsso user,pid,ppid,pgid,command
| |-- 00702 root less
| |-- 00406 root dhclient: ed0 [priv! (dhclient)
| |-- 00392 root /usr/libexec/getty Pc ttgv1
| |-- 00393 root /usr/libexec/getty Pc ttgv2
| |-- 00394 root /usr/libexec/getty Pc ttgv3
| |-- 00395 root /usr/libexec/getty Pc ttgv4
| |-- 00396 root /usr/libexec/getty Pc ttgv5
| |-- 00397 root /usr/libexec/getty Pc ttgv6
| |-- 00398 root /usr/libexec/getty Pc ttgv7
| |-- 00307 root sh /etc/rc autoboot
| |-- 00390 root sh /etc/rc autoboot

```

Copyright attribution: Uploaded by Waldo the terrible at English Wikipedia.

Copying Linux shared libraries to FreeBSD system.

Once you find the libraries, you need to open all of them in a “shadow root” directory: `/compat/linux`. Opening libraries here is essential because every time you run any Linux program on the FreeBSD system, it will look for libraries in this directory. For instance, if you run `/lib/libc.so`, the system will first look into `/compat/linux/lib/libc.so`. The system will only look into `/lib/libc.so` if it does not find the shadow root directory. All you need to do is copy the files in the last column into the `/compat/linux` directory. You will then have to link the files to the names in the first column of the above output. It will result in the following lines appearing in your FreeBSD shadow root directory:

```

/compat/linux/usr/X11/lib/libXt.so.3.1.0
/compat/linux/usr/X11/lib/libXt.so.3 -> libXt.so.3.1.0
/compat/linux/usr/X11/lib/libX11.so.3.1.0
/compat/linux/usr/X11/lib/libX11.so.3 -> libX11.so.3.1.0
/compat/linux/lib/libc.so.4.6.29
/compat/linux/lib/libc.so.4 -> libc.so.4.6.29

```

If the `/compat/linux` directory already consists of a shared library that is only a few versions old, there is no need to copy it. However, it is always safe to copy and keep the latest version. Suppose the FreeBSD system already contains the following libraries: