

WINE is not an emulator, because it does not emulate the hardware virtualisation of the host OS. Instead, it will merely collect and translate calls. Hence, where emulators become slow because of emulating entire hardware, WINE is much faster. You can say that WINE creates an interface structure that is similar to Windows.

## How to install WINE on FreeBSD?

It's essential to install some recommended prerequisites before starting with WINE. The recommended requirements include:

- **A GUI:** Windows apps are usually made with GUI at the core. Hence, whether you install it yourself or not, it will be installed automatically. But having a GUI of your choice is better.
- **Wine-gecko:** Web browsers are essential in Windows OS, and wine-gecko is a browser from Mozilla's Gecko engine, installed along with WINE if you don't do it earlier. You can install wine-gecko using the pkg tool by running the following command:

```
# pkg install wine-gecko
```

You can also compile ports to install wine-gecko:

```
# cd /usr/ports/emulator/wine-gecko
# make install
```

- **wine-mono:** The MONO framework is used to make WINE .NET compatible so that you can run all the .NET applications and programs. Similar to wine-gecko, you can install wine-mono from the pkg tool or by compiling ports. Use the following code to install from pkg:

```
# pkg install wine-mono
```

For compiling from ports, use:

```
# cd /usr/ports/emulator/wine-mono
# make install
```

Once you have all the prerequisites installed, you can head to installing WINE. Similar to other installations, you can use the pkg tool and compile ports to install WINE. To install WINE from pkg, use the following command:

```
# pkg install wine
```

To compile it from ports and install, use the below command:

```
# cd /usr/ports/emulator/wine
# make install
```

Similar to Windows, even FreeBSD comes in 32-bit and 64-bit OS. If you install WINE on 32-bit FreeBSD, it will, by default, install the 32-bit