

CODE:

- `# /etc/crontab - root's crontab for FreeBSD`
- `#`
- `# $FreeBSD$`
- `# 1`
- `SHELL=/bin/sh`
- `PATH=/etc:/bin:/sbin:/usr/bin:/usr/sbin 2`
- `#`
- `#minute hour mday month wday who command 3`
- `#`
- `*/* * * * * root /usr/libexec/atrun`

FreeBSD services

In FreeBSD, services are managed using the `rc` system. This is primarily meant to start running scripts as soon as the system initialises. The most basic commons, such as start, stop, and restart, can be controlled through the scripts included in `/etc/rc.d`. You can configure a certain service to start only if it has been enabled in `/etc/rc.conf`, or regardless of whether it has been enabled. For certain specific services, you can also reload a service after startup.

In FreeBSD, most services will depend upon the initialisation of other services. Given the same, it is essential to include information regarding file dependencies and relations, which is generally done at the top of any script as comments. These comments are parsed using the `rcorder` program, that helps decide the order in which applications will start.

The main features of any such script are:

- The `PROVIDE` keyword is an essential part of all startup scripts. The name of the service provided by the script is specified in front of this keyword.
- The `REQUIRE` keyword is used to initialise other services also required to be initialised before the current service starts. The current service will not start until these services have started.
- The `BEFORE` keyword is used to specify the dependent services of the current service. None of these services will initialise before the current service.

Network Interface Cards

When you start using FreeBSD, setting up a Network Interface Card is