

without any errors or losses in configuration data, the Network Interface Card has been set up correctly.

Virtual hosts

Virtual hosting is one of the most frequent applications for which FreeBSD is used. In this application, the same server is assigned a number of different aliases and hence appears as several different servers. You can add aliases to your network address in `/etc/rc.conf`, through a code similar to the following.

CODE:

- `ifconfig_fxp0_alias0="inet xxx.xxx.xxx.xxx netmask xxx.xxx.xxx.xxx"`

You can add several aliases to the same address, starting with `alias0` and proceeding through `alias1`, `alias2`, and so forth. As soon as you miss a number, the configuration process of your alias will come to a halt.

Alias netmasks generally need to be calculated before they are specified in a script. For any given site, one netmask must be added by the users, which is the correct representation of the actual netmask of the network. All the other addresses that are a part of the given network will have a netmask of `255.255.255.255` or `0xffffffff`.

If you are looking to configure a large number of aliases, it can be rather unrealistic to enter all subnet masks one by one. FreeBSD allows you to enter the range of network dresses you wish to cover, in which the first address represents the actual subnet mask and the others will all be assigned a subnet mask of `255.255.255.255` or `0xffffffff`. This can be accomplished using a code similar to the following.

CODE:

- `ifconfig_fxp0_aliases="inet 10.1.1.1-5/24 inet 202.0.75.17-20/28"`

System logging

To truly understand how a system works, it is important to understand system logs. System logs don't just inform you about the regular working of a system but can be of great use in case of errors and security considerations. FreeBSD contains a system logger known as `syslogd`, which starts along with the system.

The logging of system entries can be configured using `/etc/syslog.conf`. The main parameters included in this configuration file are facility and