

The `resolv.conf` file dictates the interaction between FreeBSD and the internet DNS. The following are the primary entries in this file.

- **nameserver:** This is the IP address of the server that needs to be queried.
- **search:** This is the list of domains to be searched.
- **domain:** The local domain name

```
GNU nano 2.8.4 File: /etc/ssh/sshd_config Modified
#KeyRegenerationInterval 1h
#ServerKeyBits 1824

# Ciphers and keying
#RekeyLimit default none

# Logging
# obsoletes QuietMode and FascistLogging
#SyslogFacility AUTH
#LogLevel INFO

# Authentication:

#LoginGraceTime 2m

#PermitRootLogin no
#PermitRootLogin yes

#StrictModes yes
#MaxAuthTries 6

[0] Get Help [O] Write Out [P] Where Is [X] Cut Text [J] Justify [C] Cur Pos
[X] Exit [R] Read File [W] Replace [U] Uncut Text [T] To Spell [G] Go To Line
```

Copyright attribution: tecmint

Configuration in FreeBSD

Tuning with sysctl

The `sysctl` file can be used to make changes to a running FreeBSD system. The performance of any FreeBSD system can be improved through the optimisation of `sysctl`. It contains over five hundred system variables to be assigned and read. Most system settings can be modified using it.

The `sysctl.conf` is the configuration file that is used by `sysctl`. Nearly all the variables included in `sysctl` can be assigned in the `variable = value` format. The values that have been specified are set only after the system has gone into the multi-user mode.

Certain `sysctl` values are also available only in the read-only mode. However, these values can be modified, though it is generally not recommended as it can have system-level repercussions. If you want to modify a read-only value, the system will reboot before the new value is officially assigned.

All-in-all, learning about `sysctl` is essential for all levels of users, especially experienced users who wish to get more out of FreeBSD. It doesn't just improve system performance but can also be used to create a