

```

•   data () {
•       return {
•           text: 'Hello Vue'
•       };
•   }
• }).$mount('#app')
```

The data (model) and template (view) are divided into different segments but collated together with the help of object properties.

Let us know more about the binding concept.

Interpolations

• Text

Text interpolation is the root form of data binding. You can build it using double curly braces, also known as the “Mustache” syntax. Vue is not the only program that uses these curly brackets.

```
• <div> Product: {{product}} </div>
```

The product property value replaces the double curly brackets on the corresponding data object. When there is a change in the product property of the data object, the values will be updated.

You can perform one-time interpolations with the help of the v-once directive. These do not re-render when there is a change in data. Nevertheless, this can influence the other bindings which are available on the same node.

```
• <div v-once> this will never change: {{product}} </div>
```

• Raw HTML

The double curly brackets always interpret the data as plain text and not as HTML. Use the v-html directive to have a real HTML as the output.

```
• <p>Using mustaches: {{ rawHtml }}</p>
• <p>Using v-html directive: <span v-html="rawHtml"></span></p>
```

Along with the product property value, the span contents re-renders, ignoring the data bindings and interpreting as plain HTML. Vue does not belong to the templating engine based on strings. Hence, you cannot compose template partials using v-html.

Your website can be prone to XSS attacks with dynamically rendering arbitrary HTML. Thus, it is advisable to never use HTML interpolation on user-provided content but trusted content.