

- `<!--`
- This will be converted to `v-bind:[someattr]` in in-DOM templates.
- Unless you have a `"someattr"` property in your instance, your code won't work.
- `-->`
- `<a v-bind:[someAttr]="value"> ... </a>`

Modifiers

Vue uses the Modifiers to change some of the attributes' behaviours inside the template. Represented by a dot, modifiers are special postfixes. They state that there is a special way for every directive to bind.

For example, the ***event.preventDefault()*** can be called upon when the `.prevent` modifier notifies the directive on the triggered event:

- `<form v-on:submit.prevent="onSubmit"> ... </form>`

Shorthands

Shorthands can be used the most when you feel the template takes a lot of keystrokes. The `v-` prefix defines the template with a visual cue for picking only specific attributes of the Vue. If you are using Vue.js, this will be useful when you want to patch dynamic behaviour with the given markup. However, the template may be filled with a lot of text with the use of directives.

Likewise, there is no much need to implement the `v-` prefix while composing a SPA. In SPA, every template is managed by Vue. Hence, Vue is known to offer special shorthands to two of the most prevailing directives, `v-on` and `v-bind`.

● v-on Shorthand

- `<!-- full syntax -->`
- `<a v-on:click="doSomething"> ... </a>`
- `<!-- shorthand -->`
- `<a @click="doSomething"> ... </a>`
- `<!-- shorthand with dynamic argument (2.6.0+) -->`
- `<a @[event]="doSomething"> ... </a>`

● v-bind Shorthand

- `<!-- full syntax -->`