

In this example, the computed property relies on **vm.msg**. This is because it is an observed data property in Vue. It is considered to be reactive dependence. Here, it is to be noted that whenever **vm.msg** changes, **vm.example** value would be re-evaluated.

Here, **Date.now()** is not a reactive dependency. This is because it has nothing to do with Vue and its data observation system. Therefore, when you access the **vm.example**, you will find the time stamp to be the same. It will remain the same until **vm.msg** is re-evaluated.

Sometimes, it becomes necessary to getter, where you go to access every time and access for **vm.example**. It would simply re-evaluate. Thereby, starting in 0.12.11, it would be possible to turn off caching for the particular case of computed property.

```

• computed: {
•   example: {
•     cache: false,
•     get: function () {
•       return Date.now() + this.msg
•     }
•   }
• }

```

Now, when you have access to **vm.example**, the time stamp would be up-to-date. This would only affect the programme access and inside of the JavaScript and data binding that would still be dependency-driven. Whenever you bind to the computed property in the template with **{{example}}**, the DOM would be updated when the reactive dependency changes.

```

• <div id="example">
•   <p>Original message: "{{ message }}"</p>
•   <p>Computed reversed message: "{{ reversedMessage }}"</p>
• </div>
• var vm = new Vue({
•   el: '#example',
•   data: {
•     message: 'Hello'
•   },
•   computed: {
•     // a computed getter
•     reversedMessage: function () {

```