

syntax for **v-bind:style**:

- `<div v-bind:style="[baseStyles, overridingStyles]"></div>`

Prefixing automatically

When you use a CSS property in **v-bind:style** that includes vendor prefixes, such as `turn`, Vue can automatically detect and apply the required prefixes to the implemented styles.

Multiple Values

Starting from 2.3.0 and up, you can supply an array of multiple (prefixed) values to a style object, such as:

- `<div v-bind:style="{ display: ['-webkit-box', '-ms-flexbox', 'flex'] }"></div>`

This can only show the last value in the list that the browser recognizes.

Display: flex will be rendered in this illustration for browsers that accept the unprefixed implementation of flexbox.

Conditional Class Bindings

Binding Fundamentals

We use the following syntax to bind a variable to a prop, class, or style:

```
<template>
  <span v-bind:class="className">
    Learning about conditional class bindings!
  </span>
</template>
```

Copyright Attribution:
Michael Thiessen

conditional binding

If the value of **className** is **blue-text**, the **class.blue-text** will be added to the span element. Normally, we shorten the linking syntax by deleting **v-bind**, leaving us with just this:

```
<template>
  <span :class="className">
    Learning more about conditional class bindings!
  </span>
</template>
```

Copyright Attribution:
Michael Thiessen

conditional binding