

However, the value of **className** will still be applied as a class to our **span** tag.

Guard Expressions

There is a neat trick that we can use with the logical **&&** (AND) to conditionally add a class:

```
<template>
  <span
    class="description"
    :class="useTheme && theme"
  >
    This is how you add dynamic classes in Vue.
  </span>
</template>
```

Copyright Attribution: MichaelThiessen

Logical &&

This is referred to as a guard expression.

When **useTheme** is set to **true**, the class is set to whatever the theme value is. Here, we have the boolean vector **useTheme**, and **theme** is the value of the theme class. If the first value is right, the **&&** (AND) operator in Javascript can short-circuit.

Since all values must be valid for the expression to be accurate, if the first is incorrect, there is no sense in testing whether the second is, because we already know the expression corresponds to false. As a result, if **useTheme** is set to **false**, the term evaluates to **false** and no dynamic class name is added.

If **useTheme** is set to **correct**, it will also evaluate the **theme**, and the phrase will evaluate to the theme's meaning. The value of the theme would then be used as a **classname**.

Ternaries

We may do the same thing for ternaries.

If you're not acquainted with the word, a ternary is essentially a shorthand for an **if-else** statement.

They appear as follows:

- `const result = expression ? ifTrue : ifFalse;`