

(which may delay initial rendering or impair scroll performance), virtualization concentrates on rendering only the things available to the user.

This will help maintain a quick list rendering speed on mid-range to low-end computers. As the user scrolls, you can fetch/display additional objects by unloading previous entries and replacing them with new ones.

Using v-for for List Rendering

The **v-for** directive is used to display a list of items determined by a data source. The directive may be used on a prototype feature and includes the following syntax:

v-for = "item in items"

 alias data collection
 V- for directive

Consider an example of this in action. To begin, let us assume that we already have a set of tweet data:

```
const tweets = [
  {
    id: 1,
    name: 'James',
    handle: '@loverjames',
    img: 'https://semantic-ui.com/images/avatar2/large/matthew.png',
    tweet: 'If you don't succeed, dust yourself off and try again.',
    likes: 10,
  },
  {
    id: 2,
    name: 'Fatima',
    handle: '@fantasticfatima',
    img: 'https://semantic-ui.com/images/avatar2/large/molly.png',
    tweet: 'Better late than never but never late is better.',
    likes: 12,
  },
  {
    id: 3,
    name: 'Kin',
    handle: '@keefoxin',
    img: 'https://semantic-ui.com/images/avatar2/large/elyse.png',
    tweet: 'Beauty in the struggle, ugliness in the success.',
    likes: 18,
  },
]
```

Code for V-for directive using tweets