

A tweet is a list of tweet items, each containing information about an individual tweet—a unique id, the account’s name/handle, the tweet address, and so on. Now, let’s attempt to collect tweet components based on this data using the **v-for** directive.

To begin, we’ll build the Vue instance—the application’s core. We’ll mount/attach our instance to a DOM element in the **id app** and provide the tweets collection in the data object for that instance.

We’ll now build a tweet component to be used by our **v-for** directive to make a chart. We’ll generate a component called tweet-component using the global `Vue.component` constructor:

```
new Vue({
  el: '#app',
  data: {
    tweets
  }
});
```

Creating vue

Copyright: CSS tricks

```
Vue.component('tweet-component', {
  template: `
    <div class="tweet">
      <div class="box">
        <article class="media">
          <div class="media-left">
            <figure class="image is-64x64">
              
            </figure>
          </div>
          <div class="media-content">
            <div class="content">
              <p>
                <strong>[[tweet.name]]</strong> <small>[[tweet.handle]]</small>
                <br>
                [[tweet.tweet]]
              </p>
            </div>
            <div class="level-left">
              <a class="level-item">
                <span class="icon is-small"><i class="fas fa-heart"></i></span>
                <span class="likes">[[tweet.likes]]</span>
              </a>
            </div>
          </div>
        </article>
      </div>
    </div>
  `,
  props: {
    tweet: Object
  }
});
```

Copyright: CSS tricks

V-for directive using tweets