

Where appropriate, it is advisable to use the main attribute with **v-for**, whether the iterated DOM material is easy or you deliberately depend on default actions for efficiency gains.

Because the key is a common method for Vue to classify nodes, it has additional applications unrelated to **v-for**, as we will see later in the guide.

Key

A **key** attribute is typically specified for each iterated element within a rendered **v-for** list. This is because Vue uses the main attribute to generate special bindings for the identification of each node.

Let's explain further—if our list undergoes some complex UI shifts (e.g., the sequence of list objects is shuffled), Vue would prefer to modify the data inside each unit rather than shifting the DOM entities appropriately. This is unlikely to be a concern in most situations. However, in some cases where our **v-for** list is dependent on the state of the DOM and/or child component, this may result in some unexpected actions.

We'll incorporate this new input area into the tweet-template components as follows:

```
Vue.component('tweet-component', {
  template: `
    <div class="tweet">
      <div class="box">
        // ...
      </div>
      <div class="control has-icons-left has-icons-right">
        <input class="input is-small" placeholder="Tweet your reply..." />
        <span class="icon is-small is-left">
          <i class="fas fa-envelope"></i>
        </span>
      </div>
    </div>
  `,
  props: {
    tweet: Object
  }
});
```

Copyright: CSS tricks

Tweet component

Assume we wanted to add another new function to our application. This functionality will encourage the consumer to arbitrarily scramble a collection of tweets.