

```

01  /* Selecting DOM element */
02  const button = document.querySelector("button");
03
04  /* Callback function */
05  function alertButton() {
06      alert('Hi native JavaScript');
07  }
08
09  /* Event listener */
10  button.addEventListener("click", alertButton, false);

```

Copyright Attribution: Envato Tuts+

Javascript event listener

Finally, the event listener is added. Using the dot notation, we must always append the **addEventListener()** method to a pre-selected DOM variable. We specify the event we want to listen to (“click”), then the name of the callback feature (**alertButton**), and finally the meaning of the **useCapture** parameter in the parameters.

How to Enable All Buttons Functionality

As a result, the code above applies the alert function to the page’s first key. But how will we go about making both buttons have the same functionality? To accomplish this, we’ll use the **querySelectorAll()** process, loop through the items, and assign an event listener to each button:

```

01  /* Selecting DOM nodelist */
02  const buttons = document.querySelectorAll("button");
03
04  /* Callback function */
05  function alertButton() {
06      alert('Hi native JavaScript');
07  }
08
09  /* Event listeners */
10  for (let button of buttons) {
11      button.addEventListener("click", alertButton, false);
12  }

```

Copyright Attribution: Envato Tuts+

Adding querySelectorAll()

We must loop through the nodes to add a click event listener to each button since **querySelectorAll()** returns a **NodeList** rather than a single