

element. The code above, for example, would produce three click event listeners if there are three buttons on the page.

With **addEventListener()**, you can only listen to one event at a time. You'll need to build a second event listener rule if you want the custom **alertButton()** feature to fire on a certain event kind, such as mouseover:

```
1  /* Event listeners */
2  for (let button of buttons) {
3      button.addEventListener("click", alertButton, false);
4      button.addEventListener("mouseover", alertButton, false);
5  }
```

Copyright Attribution:
Envato Tuts+

Adding addEventListener()

Event Handlers

Events are signals sent from inside the application window that alert the user to changes in the browser or operating system. Event handler code may be written by programmers to operate when an event occurs, enabling web pages to react correctly to changes.

Properties of event handlers

The event handler property used in this case is the **onclick** property. It's exactly the same as any other property on the button (for example, **btn.textContent** or **btn.style**), but it's a rare type in that when you configure it to be identical to a code, the code is executed when the button's event fires.

There are several event handler properties to choose from:

- **btn.onfocus** and **btn.onblur** — As the button is focused and unfocused, the colour changes; click the tab to focus on the button, then press the tab again to focus away from it. When they are oriented, they are often used to show details regarding filling in form fields or to display an error message if a form field is filled with an incorrect value.
- **btn.ondoubleclick** — Just when the icon is double-clicked does the colour shift.
- **window.onkeypress**, **window.onkeydown**, and **window.onkeyup** — As a key on the keyboard is pushed, the colour switches. The keypress event denotes a full press (button down, then up), while keydown and keyup denote just the key down and key up portions of the keystroke, respectively. Note that registering this event handler on the button itself would not work; however, we must register it on the window variable, which reflects the entire browser window.