

- **btn.onmouseover** and **btn.onmouseout** — The colour of the icon varies as the mouse cursor hovers over it or pushes away from it, respectively.

Event Modifiers

Within event handlers, calling **event.preventDefault()** or **event.stopPropagation()** is a standard requirement. While we can do this conveniently inside methods, it would be preferable if the methods should focus solely on data logic rather than DOM case specifics.

Vue offers event modifiers for **v-on** to solve this problem. Remember the modifiers are dot-denoted directive postfixes.

- .stop
- .prevent
- .capture
- .self
- .once
- .passive

```

<!-- the click event's propagation will be stopped -->
<a v-on:click.stop="doThis"></a>

<!-- the submit event will no longer reload the page -->
<form v-on:submit.prevent="onSubmit"></form>

<!-- modifiers can be chained -->
<a v-on:click.stop.prevent="doThat"></a>

<!-- just the modifier -->
<form v-on:submit.prevent></form>

<!-- use capture mode when adding the event listener -->
<!-- i.e. an event targeting an inner element is handled here before being handled -->
<div v-on:click.capture="doThis">...</div>

<!-- only trigger handler if event.target is the element itself -->
<!-- i.e. not from a child element -->
<div v-on:click.self="doThat">...</div>

```

Copyright Attribution: Vue.js

Use of event modifiers

When using modifiers, the order is important since the relevant code is created in the same order. As a result, **v-on:click.prevent.self** prevents all clicks, while **v-on:click.self.prevent** prevents just clicks on the feature itself.