

The **.passive** modifier in Vue corresponds to the passive alternative in `addEventListener`.

```
<!-- the scroll event's default behavior (scrolling) will happen -->
<!-- immediately, instead of waiting for 'onScroll' to complete -->
<!-- in case it contains 'event.preventDefault()' -->
<div v-on:scroll.passive="onScroll">...</div>
```

Copyright Attribution: Vue.js

.passive modifier

The **.passive** modifier is particularly useful for optimising mobile device efficiency.

If you use **.passive** and **.prevent** at the same time, **.prevent** will be skipped, and your window will most likely show an alert. Remember that, passive tells the browser that you don't want the event's default behaviour to be overridden.

Key Modifiers

We frequently need to look for specific keys while listening for keyboard events. When listening for important events, Vue helps you to apply key modifiers to **v-on**:

```
<!-- only call 'vm.submit()' when the 'key' is 'Enter' -->
<input v-on:keyup.enter="submit">
```

Copyright Attribution: Vue.js

Using v-on.

Event bubbling and capture

When two handlers of the same event form are triggered on the same element, event bubbling and capture are two mechanisms that characterise what happens. To make it simpler, let's look at an illustration.

```
<button>Display video</button>

<div class="hidden">
  <video>
    <source src="rabbit320.mp4" type="video/mp4">
    <source src="rabbit320.webm" type="video/webm">
    <p>Your browser doesn't support HTML5 video. Here is a <a href="rabbit320.mp4">link to the video</a> instead.</p>
  </video>
</div>
```