

/proc — Kernel and Process Files

Because it does not include standard files, the /proc folder is identical to the /dev folder. It has unique files that reflect system and process data.

/root — Root Home Directory

The root user's home directory is located in the /root directory. It is now placed at /root rather than /home/root. /root should not be confused with /, which is the system's root folder or directory.

/run — Application State Files

The /run folder is very new. It provides a common location for programs to store transitory files such as sockets and process IDs. Because files in /tmp could be removed, some files cannot be saved in /tmp and are instead saved on /run.

/sbin — System Administration Binaries

The /sbin folder is identical to the /bin folder in terms of functionality. It includes important binaries for system management that the root user often runs.

/SELinux — SELinux Virtual File System

If your Linux version utilizes SELinux for security (for example, Fedora and Red Hat), then /SELinux directory includes SELinux-specific files. It is comparable to the command /proc. Ubuntu does not employ SELinux. The existence of this subdirectory looks to be a problem in Ubuntu.

/srv — Service Data

The /srv directory stores data for system services supplied by the system. If we were using an Apache HTTP server to host a website, the /srv folder would most likely have the website files.

/tmp — Temporary Files

The /tmp directory is used by applications to store temporary files. These files are usually destroyed when your system is rebooted.

/usr — User Binaries & Read-Only Data

Users' apps and files are stored in the /usr folder.