

Run two command in background, simultaneously:

```
$ apt-get update & apt-get upgrade &
```

2. semi-colon Operator (;)

The semi-colon operator makes it possible to run, several commands in a single go and the execution of command occurs sequentially.

```
$ apt-get update ; apt-get upgrade ; mkdir test
```

The above command combination will first execute update instruction, then upgrade instruction and finally will create a 'test' directory under the current working directory.

3. AND Operator (&&)

The AND Operator (&&) would execute the second command only, if the execution of first command SUCCEEDS.

For example, I want to visit website digit.in using links command, in terminal but before that I need to check if the host is live or not.

```
$ ping -c3 www.digit.in && links www.digit.in
```

4. OR Operator (||)

The OR Operator (||) is much like an 'else' statement in programming. The above operator allow you to execute second command only if the execution of first command fails.

For example, if you want to execute 'apt-get update' from a non-root account and if the first command fails, then the second 'links www.digit.in' command will execute.

```
$ apt-get update || links digit.in
```

5. NOT Operator (!)

The NOT Operator (!) is much like an 'except' statement. This command will execute all except the condition provided. To understand this, create a directory 'skoar' in your home directory and 'cd' to it.

```
$ mkdir skoar
```

```
$ cd skoar
```

Next, create several types of files in the folder 'skoar'.

```
a.doc b.doc a.pdf b.pdf a.xml b.xml a.html b.html
```

See we've created all the new files within the folder 'skoar'.

```
$ ls
```

```
a.doc a.html a.pdf a.xml b.doc b.html b.pdf b.xml
```