

For example, check if a directory 'bin' is available or not, and output corresponding output.

```
$ [ -d bin ] || { echo Directory does not exist, creating
    directory now.; mkdir bin; } && echo Directory exists.
```

9. Precedence Operator ()

The Operator makes it possible to execute command in precedence order.

```
Command_x1 &&Command_x2 || Command_x3 && Command_x4.
```

In the above pseudo command, what if the Command_x1 fails? Neither of the Command_x2, Command_x3, Command_x4 would executed, for this we use Precedence Operator, as:

```
(Command_x1 &&Command_x2) || (Command_x3 && Command_x4)
```

In the above pseudo command, if Command_x1 fails, Command_x2 also fails but Still Command_x3 and Command_x4 executes depends upon exit status of Command_x3.

10. Concatenation Operator (\)

The Concatenation Operator (\) as the name specifies, is used to concatenate large commands over several lines in the shell. For example, The below command will open text file filename(3).txt.

```
$ nano filename\ (3\ ) .txt
```

Conclusion

Knowing these operators and Linux commands not only helps in getting more information about file management but also about how certain terminal commands can be used efficiently in particular scenarios. We have listed a few common commands that can be used in pairs as well. Some of these commands can help beginners, but the majority of them are for experienced people. What's ultimately more important is that it makes your work easier and faster!

This section is mostly focused on terminal commands for Linux users. Windows and Mac have different ways and terminal commands to deal with tasks. Therefore, ensure to put these commands in your list and use them while working on your next task on Linux. **d**