

with an account UID 0. These users have complete access to the system and help in doing everything.

```

• [user01@host]$ ps -au
• USER          PID %CPU %MEM    VSZ   RSS TTY      STAT START
TIME COMMAND
• root           777  0.0  0.0 225752 1496 tty1      Ss+  11:03
0:00 /sbin/agetty -op -- \u --noclear tty1 linux
• root           780  0.0  0.1 225392 2064 ttyS0      Ss+  11:03
0:00 /sbin/agetty -op -- \u --keep-baud 115200,38400,9600
• user01         1207  0.0  0.2 234044 5104 pts/0      Ss   11:09
0:00 -bash
• user01         1319  0.0  0.2 266904 3876 pts/0      R+   11:33
0:00 ps au

```

Every system has a system user account. It can be one or more depending upon the user. It helps in providing support services to the user and accomplishes several processes. These are again categorized further as there are types in this as well.

What is a Group?

To define a group, we can simply say that it is a complete collection of different users who have to share access to some system resources, files, and other resources. A group doesn't need to grant access to a single user because there are cases when it is used in places where a set of users need access to these files. Furthermore, this can become a bit chaotic on your computer. However, to keep it different, different names are given to the groups just like the users. This not only helps in segmenting things but also makes the identification of a particular group easier. The computer identifies the groups using the same UID number as they are assigned to users.



```

root@JavaTpoint: ~
root@javaTpoint:~# useradd -D
GROUP=100
HOME=/home
INACTIVE=-1
EXPIRE=
SHELL=/bin/sh
SKEL=/etc/skel
CREATE_MAIL_SPOOL=no
root@JavaTpoint:~#

```

Copyright attribution: <https://www.javatpoint.com/linux-user-management>

The grouping in a system acts similar to that of the user. Although there are a few similarities, they are majorly different.