

When it comes to mapping the GID group names, it can be defined in the database of your group account. By default, the system uses the `/etc/group` file to store all the information about the local groups. Each line in the `/etc/group` file will contain information as well as data about one group. There are several group entries in the entire system. Each of these entries is divided into four separate fields; these are also the four colon-separated fields.

User and Group Configuration Files

1. `/etc/passwd`

Whenever a new user gets added to the management, all the information is stored with the colon-separated line that is given in the above command. Given below is an example that can be used by the user

- `# tail -1 /etc/passwd`
- `test:x:1001:1001:test user:/home/test:/bin/bash`

2. `/etc/shadow`

Regarding user and group management, several things have to be considered; this code is one of them. The users having a shadow password will have a benefit. With accounts having such passwords, a new entry gets created each time a new user is created in the directory. The other benefit that comes with this password is that these files can be viewed by the root users only. Listed below is one such example to explain you better:

- `# tail -1 /etc/shadow`
- `test:$6$XBCDBQ...:17610:0:99999:7:::`

3. `/etc/group`

If you are still not aware, Oracle Linux uses the UPG scheme that uses this command. With the help of this, a new entry gets created automatically whenever a user is added. Moreover, when an entry gets created, it is done with the same username to understand which amongst them belong to the same group. Below is an example to explain the same.

- `# tail -1 /etc/group`
- `test:x:1000:test`

4. `/etc/gshadow`

Now, this is a code for hashed group passwords. It is stored in the same file but is rarely used. Being a group password, it is considered to be a bit