

complex; that is the reason why it is less used. To know and understand it better, here is an example for the same:

- `# tail -1 /etc/gshadow`
- `test:!!!:test`

All these commands and examples are for the configuration files of groups and users. These are part of the entire group and user management ecosystem.

Adding any User Account

Useradd is the command that helps in adding the user account to the directory. Here is the syntax for the same:

- `# useradd [options] user_name`

Conversely, when a new user is created, the default settings are applied in the directory. Therefore, this example will help you in understanding this better.

- `# useradd john`
- `# tail -1 /etc/passwd`
- `john:x:501:501::/home/john:/bin/bash`



```

root@JavaTpoint:~# tail -2 /etc/passwd
jtp:x:1001:1001:::/home/jtp:/bin/ksh
guest-on3h5B:x:118:128:Guest,,,:/tmp/guest-on3h5B:/bin/bash
root@JavaTpoint:~#

```

Copyright attribution: <https://www.javatpoint.com/linux-user-management>

When it comes to group management systems, there is an entire ecosystem to understand.

However, when there is a default username getting created, it adds a locked account for the user. If you want to unlock the account and also assign the password to that account, you will have to run “passwd user_name” in the root command. An example to understand this:

- `# passwd john`

This command prompts you to create a new password and depending upon the complexity of the created password, you will be notified. It works the same as any other password-making account; you will be notified about the same: if your password is weak, moderate, or strong. You can change it, and then re-enter the password; continue with the same password to unlock your user account. This is also the way to not only create a password but also change it.