

```
$kill 6738
```

```
Terminated
```

The kill command terminates the first process. In case a process ignores this command, you can use the kill-9 command followed by the process ID as mentioned here:

```
$kill -9 6738
```

```
Terminated
```

Types of Processes

This section tries to break down some of the important processes you will encounter in Linux. These processes are essential to understand the functioning of your code, and thereby the entire program.

1. **Parent Processes:** Any process that uses the Fork() System call is the parent process. Simply put, a process can have only one parent (parent process) and multiple children (child processes). At the beginning of a process, the parent process is with an ID, aligning with its respective child processes later in the process. This makes it easier to scan the code and identify the child and parent processes.
2. **Child Processes:** By definition, a child process is created by another process (called the parent process). You may also understand a child's process as a subprocessor—a subtask of the bigger process. Like a child, it inherits most of the attributes of its parents.
3. **Orphan Processes:** When the parent process executes or terminates before the child process, the child process becomes an orphan process. In this scenario, the init process takes the role of a parent process. This is also called re-parenting, which is in most cases usually initiated. Even after the init process adopts the child process, it continues to be an orphan process since the initial parent processes do not exist anymore.
4. **Zombie Processes:** As the name suggests, zombie processes (also known as the defunct processes) are the dead processes that aren't cleaned up efficiently. Here, the programs stick around, with or without creating the output they were supposed to. While creating a UNIX fork system call process, the parent process' address space is replicated. Unlike in orphan processes, the child process is terminated, and the parent process is not. Here, the terminated child process becomes a zombie process. This usually happens when a parent process isn't programmed clearly.