

Mounting is a process in which a physical file is drawn up for access and given a location in the filesystem. Fstab saves time here and also helps to avoid order errors. Every line has six fields separated by tabs or spaces. If you wish to add a new device or repartition the old one, you will have to modify the file. We will understand the various fields in the following sections.

```
#
# /etc/fstab
# Created by anaconda on Thu Jul 25 19:06:59 2013
#
# Accessible filesystems, by reference, are maintained under '/dev/disk'
# See man pages fstab(5), findfs(8), mount(8) and/or blkid(8) for more info
#
# device name  mount point  filesystem_type  mount_option  dump  file_check
/dev/sda1      /             ext4             defaults      1      1
/dev/sda2      /rr           ext4             defaults      0      0
/dev/sda3      swap          swap             defaults      0      0
```

here we defined that /dev/sda2 will be mounted on /rr directory and format of this partition is ext4 and mount option is setting to default put value of dump and file check 0 because its normal partition and we dont need to check mark it

/dev/sda3 is swap partition whose file mount point is nothing because its swap and its format is also swap put value of file check 0 because its like RAM so nothing will be store here

-- INSERT --

Copyright attribute: <http://www.manulinux.org/2013/08/etcfstab-file-how-mounting-of.html>

Usage of various commands in fstab file

Table format

The table is made in a six-column structure. Each column has a specific parameter. It is crucial to set the columns in the correct order. These six columns are:

1. **Device** - UUID of the device. It has a file system.
2. **Mount point** - It is the directory of the root file that enables you to read the device's content.
3. **Filesystem type** - It specifies the type of filesystem that is being used.
4. **Options** - It specifies the active mount points.
5. **Backup operation** - This is an outdated system that is not used anymore. Usually, it is set to 0, which disables any backup.
6. **Check order** - These have three numbers. If set at 0, the fsck (File System Consistency Check) command will not check the order. With any number