

### Step 1: Make a list of the partition schemes

Run the following command to list the partition scheme before removing a partition.

### Step 2: Pick a disk

Choose the disk containing the partition you want to remove.

Run the following command to choose a disk:

- `sudo fdisk /dev/sdb`

```
nevena@nevena-VirtualBox:~$ sudo fdisk /dev/sdb
Welcome to fdisk (util-linux 2.34).
Changes will remain in memory only, until you decide to write them.
Be careful before using the write command.

Command (m for help):
```

Copyright attribution:  
Pheonixnap

Pick a disk

### Step 3: Delete Partitions

Back up your data before removing a partition. When a partition is removed, all the data is immediately erased.

```
Command (m for help): d
Selected partition 1
Partition 1 has been deleted.

Command (m for help):
```

Copyright attribution:  
Pheonixnap

Deleting partitions

To remove a partition, use the Fdisk command-line utility's `d` command. If there are no other partitions on the disk, the partition is automatically chosen. If the disk has several partitions, choose one by entering its number. The terminal displays a message indicating that the partition has been erased.

### Step 4: Confirm Partition Removal

To ensure that the partition has been removed, reload the partition table. Run the `p` command to do this.

The partition structure of the disk chosen in Step 2 is printed by the terminal. Reload the partition table.