

In this section, we will create the login digit and the password Pass@123.

```
$ sudo mysql -e "CREATE USER 'digit'@'localhost' IDENTIFIED BY 'Pass@123';"
```

Then, test mysql access by using the below command with the newly established login and password.

```
$ mysql -u digit -p
```

```
Enter password: "Type password here"
```

Once the password is verified, you'll see the following on the console:

```
Welcome to the MySQL monitor.  Commands end with; or \g.
Your MySQL connection id is 12
```

```
Server version: 5.7.22-0ubuntu18.04.1 (Ubuntu)
```

```
Copyright (c) 2000, 2018, Oracle and/or its affiliates. All
rights reserved.
```

```
Oracle is a registered trademark of Oracle Corporation
and/or its
```

```
affiliates. Other names may be trademarks of their respective
owners.
```

```
Type 'help;' or '\h' for help. Type '\c' to clear the cur-
rent input statement.
```

To exit, type:

```
mysql> exit
```

Installation of PHP

After installing Apache and setting up the virtual host perfectly on your machine, you can now install PHP. Apache server helps in serving relevant and requested content to the user, while MySQL helps in storing and managing data. Apart from this, PHP helps in displaying dynamic content to the user.

To set up PHP on your machine, you may need both PHP and MySQL packages. This allows PHP components to communicate with MySQL-based databases. However, to enable Apache for handling PHP files, you may need libapache2-mod-PHP. When you install the Apache library, the core PHP packages will get automatically installed as dependencies.

Steps to Install and Verify PHP Installation

The downloaded Apache package "libapache2-mod-php" has to be installed on the Apache server. For this, you can use the following command:

```
$ sudo apt install php libapache2-mod-php php-mysql
```