

computer to handle more data at once. This will help you if you have a fast Internet connection (greater than 10 Mbps). If you have a slower Internet connection, you might not notice any difference at all, so avoid this.

In most cases, your system's network stack allocates 15 IRPs. Although you can arrange up to 50, you'll almost always benefit more with 32. First, try 32.

Here's the location of the key in your registry:

```
\HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Lanman\Server\Parameters
```

On the right side of the regedit window, add "IRPStackSize" as a DWORD value, change the base to "Decimal," and adjust the value to 32.

SizReqBuf

The size of the raw receive buffers in a server context is represented by SizReqBuf. This indicates that your capacity to host something in a high-latency environment will be harmed. Assume you're running a game server where a lot of users are complaining about lag. This number can be changed to help lessen the impact of lag. If you're hosting a website or providing any other service, such as delivering files over instant messenger or Neo Modus Direct Connect, you'll benefit as well.

Normally, your system allocates 16384 bytes to this buffer. This is plenty for most servers, but if you have a little amount of memory, you may be unable to keep up with the high request traffic.

Here's the location of the key in your registry:

```
\HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Lanman\Server\Parameters
```

On the right side of the regedit window, add "SizReqBuf" as a DWORD value. If your server has more than 512 MB of physical memory, increase the amount to 17424. If your machine has less than 512 MB of memory, you should consider upgrading, but you can change this amount to 4356 in the meantime.

DefaultTTL

Time to Live (TTL) instructs routers how long a packet should stay in the air before giving up and discarding it during delivery attempts. When the value is frequently high, your computer will spend more time waiting for a failed packet to arrive, ultimately lowering network productivity.