

The location where “MaxUserPort” must go is in the following registry path:

```
\HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Parameters
```

Create a value called “MaxUserPort” with the value 65534. That’s it!

GlobalMaxTcpWindowSize

This setting has a long name, but if you have a fast Internet connection (10 Mbps or above) and frequently upload files, you won’t regret changing it. This value indicates how much data your computer may send before getting an acknowledgement (ACK) packet.

Every time you send little amounts of data over the Internet, your computer must wait for this packet, which informs the other end of the network that “all is well!” “Please send more!” This may not always be ideal due to latency and inadequate peering. As a result, you can change this number to allow more data to be transferred without having to wait for that packet.

Create a DWORD called “GlobalMaxTcpWindowSize” in the following registry path:

```
\HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\
Tcpip\Parameters
```

You’re done once you’ve set the value to 65535. The computer will now be able to communicate 64 kilobytes without having to wait for an acknowledgement. If you observe a decrease in network performance after changing this setting, either remove the value or increase it slightly to 128 kilobytes (by setting the value to 131072).

MTU

MTU has a greater impact on upstream speed than downstream speed, but upstream is just as crucial in terms of ensuring that larger chunks of data are transferred at once. While your network card usually sets this amount for you, you can change it based on your Internet connection speed.

This is a difficult value to set. To begin, determine your ideal MTU value, which is one that does not necessitate packet fragmentation due to your Internet connection speed limits.

You can do this by going to the Command Prompt and entering the following:

```
ping -f -l <mtu> <your gateway>
```