

But.. considering we want to have it available in every terminal we open, we use to have a “shortcut”, which is adding this command to the file “/home/<user>/.bashrc”. The .bashrc file is called every time a new terminal is opened, therefore, we won’t need to source ROS setup, since we have the instruction in this file. In order to add the command to the file, you can edit it manually using an editor of your preference or just execute the command below:

- `echo "source /opt/ros/melodic/setup.bash" >> ~/.bashrc`

Test it out

At this point, we must have everything in place. Let’s try some ROS commands to make sure the installation has finished successfully.

If you have the same terminal opened from the beginning, consequently, you have to execute the source for your .bashrc file to have ROS commands available.

- `source ~/.bashrc`

And if you have added it to your .bashrc file, that’s the last time you will execute it.

The first thing we should try it running roscore. In other words, we will run the process in charge of communicating everything ROS-related in a ROS environment.

- roscore
- ... logging to /home/ubuntu/.ros/log/c70b2cce-e773-11e9-9f15-027a087bcd00/roslaunch-ip-172-31-31-24-15073.log
- Checking log directory for disk usage. This may take awhile.
- Press Ctrl-C to interrupt
- Done checking log file disk usage. Usage is <1GB.
- started roslaunch server http://ip-172-31-31-24:45551/
- ros_comm version 1.14.3
-
- SUMMARY
- =====
-