

IDES FOR PYTHON

Here we introduce you two of the Python environments used commonly.

1. NETBEANS

Installing NetBeans

Although NetBeans is included in Ubuntu repositories, everything described here was tested with NetBeans 6.9.1.

- Go to <http://www.netbeans.org/>
- Click on “Download FREE (NetBeans 6.9.1)” in the middle of the page
- Download the C/C++ bundle
- If <http://www.netbeans.org/> is experiencing problems, try e.g. <http://dlc.sun.com.edgesuite.net/netbeans/6.9.1/final/bundles/netbeans-6.9.1-ml-cpp-linux.sh> (MD5 sum from <http://www.netbeans.org/> is 26f585185b95682cb07d3e5218760702)
- Run (as root) the downloaded file (install script and embedded archive)
- ```
1 $ sudo sh netbeans-6.9.1-ml-cpp-linux.sh
```

#### Getting ROS environment variables in NetBeans

NetBeans can “import” project from existing sources. It can use Makefiles, and even run configure script or CMake to generate one. But, that kind of automatic project configuration and build would overwrite stub makefile that every ROS package has. That makefile in essence runs ROS build system for a package, and that is what we want NetBeans to do.

In order to use rosmake from NetBeans, we need to set ROS environment variables in NetBeans. Since NetBeans is started with a shell script on Linux, we can include the variables in the script.

Since from recent versions rosininstall generates setup.sh, setup.bash and setup.zsh (as opposed to just setup.sh which was actually a bash script), there is no need for all the steps that are described in the next section.

The following will suffice to get ROS environment variables to NetBeans:

- ```
1 $ roscd
```
- ```
2 $ cd ..
```
- ```
3 $ echo ". $(pwd)/setup.sh" > ~/.netbeans/6.9/etc/netbeans.conf
```

We don't actually need perks specific to bash.